



This is a overview of removing scratches and doing touch up paint repair in the same area. The DVD & Quick Start Guide cover removing scratches. The videos on the website covers the techniques for applying touch up paint.

You can also view this video at <http://www.car-scratch-remover.com/touch-up-paint-video-page/>

Or www.CarScratchRemoverBlog.com in the “how to” video section.

Accessories can be found at www.CSRstore.com

The Ultimate Car Scratch Remover System: (DVD + Quickstart guide)

1. Clean the area per videos (step 1).
2. Remove as much of the scratches in the clear coat as possible. The idea is to make the area as shiny as possible...prior to applying touch up paint. DO NOT apply Evening Glass Glaze and Sacred Shine Sealant at this point. You will only use Totally Bitchin' Scratch Remover. (only steps 1-3)

Optional step# 4 (Safe-T-Sand):

You may need to use the Safe-T-sand, if necessary. Use it per the instructions/video you may only need one 5sec application followed by (one or two apps) of Totally Bitchin Scratch Remover. The side benefit is that the SafeTsand will ever so slightly take any sharp edges off a deep scratch that will need touch up paint.

Up to this point you will have only used the Totally Bitchin' Scratch Remover polish.

(OPTIONAL KIT) The Touch Up Paint System:

3. You can use the smaller of the two chamois in the touch up kit and apply a little pre-cleaner just to the scratch itself to make sure there is no polish residue in it for good paint adhesion.
4. Follow the DVD tutorial on applying touch up paint.

After you have done the touch up to your satisfaction (whether you did the entire touch up kit solvent process or just applied touch up paint) wait about a day or two for the paint to fully dry. Because touch up paint does not have a hardener...so depending on the prevailing temps a day or two should be fine before proceeding to the next steps.

If you **are not** using the optional Touch Up Paint kit solvents to level a touch up paint blob you can use the Safe-T-Sand accessory after spot sanding with “wine cork” spot sanding tool. You will need to allow the touch up paint 24-48 hrs of cure time.

The Ultimate Car Scratch Remover System: (DVD + Quickstart guide)

5. Apply Evening Glass Glaze (step #5) to the entire area per the instructions. Do the entire door, fender etc...it makes the whole area look nice. (ensure the entire area is clean and grit free)
5. Apply Sacred Shine Sealant to the entire door, fender etc area per the instructions.



HOT Tip 1: Before you do any touch up paint work make sure you have a high quality lacquer thinner on hand, a pint will last you forever! Ace Hardware, Home Depot etc...just make sure it is the highest quality they have (or automotive paint quality).

The lacquer thinner is the only thing that will clean touch up paint from your original finish **WITHOUT** harming the car finish. Use a clean soft terry cloth (or one of the blue industrial wipes in the touch up kit) and **just be gentle**. The great thing is that you can redo the touch up paint application as many times as it takes to get it perfect.

HOT Tip 2: Applying the touch up paint surgically will yield the nicest looking repair...and if you lay it down perfect with hardly any overlap or “blob” you will not even need to use the “blob” solvent to flatten it out. And this is the secret...put the paint on so nicely that you don’t even need to use the “blob” solvent to level the touch up paint. The less you have to mess with the touch up paint after applying it, the better.

HOT Tip 3: You can use the Safe-T-Sand to level a touch up paint blob. Be very careful you do not sand into the surrounding paint. The Safe-T-Sand is designed to conform to a surface when compared to a rubber sanding block...take care when sanding. Its best used after spot leveling sanding with the “wine cork” tool.

HOT Tip 3: After you have removed scratches and done touch ups you can apply the Bonus Sealant to the entire car...and get ready for a slick shine you will not believe. Just wait a few days after all the repairs and wash and completely dry the entire car and go for it. The sealant is extremely easy to apply and buff...way easier than a traditional paste wax...it will protect for 6-8 months.

HOT Tip 4: Most touch ups rarely need clear and tend to come out the nicest with just the color applied.

ENJOY!